

# Microstructure and Mechanical Properties of Ternary Eutectic V-Si-B Alloys

**Hasemann, G.<sup>1</sup>; Yang, W.<sup>2</sup>; Schwaiger, R.<sup>2</sup>; Krüger, M.<sup>1</sup>**

<sup>1</sup>Otto-von-Guericke University Magdeburg, Institute of Materials and Joining Technology

<sup>2</sup>Forschungszentrum Jülich GmbH, Institute of Energy and Climate Research, Microstructure and Properties of Materials (IEK-2)

The V-Si-B system has gained scientific interest as a new low-density, refractory metal-based structural intermetallic alloy system. The alloy design is strongly influenced and driven by the developments in the field of Mo-Si-B alloys and shares some interesting structural and microstructural features. Very recently, the formations of ternary eutectic  $V_{SS}$ - $V_3Si$ - $V_5SiB_2$  microstructure has been reported [1] which contains the same isomorphous phases as the ternary eutectic in the well-studied Mo-Si-B system: a refractory metal-based solid-solution phase ( $Mo_{SS}$  or  $V_{SS}$ ) and the two intermetallic phases with either an A15 ( $Mo_3Si$  and  $V_3Si$ ) or a D8<sub>1</sub> ( $Mo_5SiB_2$  and  $V_5SiB_2$ ) structure. In contrast to the Mo-based system, where the intermetallic  $Mo_3Si$  represents the major phase within the ternary eutectic microstructure, the  $V_{SS}$ - $V_3Si$ - $V_5SiB_2$  eutectic features the ductile solid-solution phase as the major component. This fact makes the V-Si-B ternary eutectic very interesting in terms of its mechanical properties. The present work is focused on the compressive stress-strain behavior of different near-eutectic V-Si-B alloy. Compression tests were performed using an electro-mechanical universal testing machine and a constant crosshead speed corresponding to an initial (engineering) strain rate of  $10^{-3} s^{-1}$ . The yield stresses were determined by the 0.2% offset method. The temperature dependence of its yield stress between room temperature and 1000 °C was investigated in the as-cast and annealed state (1400 °C for 100 hrs) of the fully eutectic alloy V-9Si-6.5B and were compared to literature values of different V-based alloys [2–4].

## References:

- [1] W.G. Yang, G. Hasemann, M. Yazlak, B. Gorr, R. Schwaiger, M. Krüger, J. Alloys Compd. 902 (2022) 163722.
- [2] H. Bei, E.P. George, E.A. Kenik, G.M. Pharr, Z. Met. 95 (2004) 505–512.
- [3] S. Xie, E.P. George, MRS Proc. 980 (2007) 0980-II08-05.
- [4] M. Krüger, Scr. Mater. 121 (2016) 75–78.